SLT Digital Spirit Electronic Ltd., ShenZhen CN

TP05 Serials Touch Screen Controller

- SLT-TP05
- SLT-TP05-USB
- SLT-TP05-RS232
- **TP05-5W-USB**
- TP05-5W-RS232

Customer Name : _____ Date: The TP05 serials of of 4-Wire/5-Wire Analog Resistive TouchScreen Controller provides the optimistic performance of touch panels. It include 4 kinds products:SLT-TP05-USB ,SLT-TP05-RS232, TP05-5W-USB ,TP-05W-RS232; It communicates with PC directly through USB port ,or RS232.. The touch panel driver emulates mouse left and right button function and supports operation systems including Windows 95 / 98 / ME / NT4 / 2000 / XP / XP Tablet PC Edition, Windows CE2.12 / 3.0 / .NET, DOS, Linux and iMac.

Specifications for TouchKit Controller:

- Power requirements: +5VDC (Maximum 100mA, typical 70mA, 50mV peak to peak maximum ripple)

- Operating temperature: 0 to 50 C
- Protocol: USB 1.1 Low speed
- Resolution: 2048 X 2048
- Report rate: Max. 160 points/sec
- Response time: Max. 35 ms
- Panel resistance: 200 ~ 900 ohm (pin to pin on the same layer)
- Dimensions: 0.79 in x 2.7 in
- Storage Temp. -50 ° C to 25° C
- Operating Temp. 0 $^\circ$ C to 70 $^\circ$ C

Features for TouchKit Software

- Calibration: Fast full oriental 4 points position
- Compensation: Accuracy 25 points linearity compensation

- Mouse Emulator: Right / Left button emulation, Normal / Click on touch / Click on release mode, Auto right button

- Extend Feature: Support monitor / display rotation, Support multiple monitor / display, Support QVGA and Half-VGA function, Support edge compensation

External Data Line

SLT-TP05-RS232


Product Photo:







Controller

PC



Power supplied from ps2 socket





1: DATA 2: 3: GND 4: VCC 5: Clock 6:

2: RX 3: TX

5: GND

SLT-TP05-USB


Product Photo:






D-: WHIETE D+:GREEN, GND:BLACK , VCC:RED, GND:BLACK

TP05-5w-usb



TP05-5w-rs232



RS232 Line Connected is same as slt-tp05-rs232